

CONDUCTOR TIPO THW

TABLA DE DATOS TÉCNICOS Cu DESNUDO TEMPLE DURO

CALIBRE CONDUCTOR mm ²	Nº HILOS	DIÁMETRO HILO mm	DIÁMETRO CONDUCTOR mm	ESPESOR AISLAMIENTO mm	DIÁMETRO EXTERIOR mm	PESO Kg/Km	AMPERAJE (*)	
							AIRE A	DUCTO A
4	7	0.84	2.44	0.8	4.1	47	40	30
6	7	1.02	2.98	0.8	4.6	67	52	38
10	7	1.33	3.99	1.1	6.2	117	78	55
16	7	1.69	4.67	1.5	7.7	186	110	75
25	7	2.13	5.88	1.5	8.9	278	140	95
35	7	2.51	6.92	1.5	10	375	175	120
50	19	1.77	8.15	2	12.3	520	215	140
70	19	2.13	9.78	2	13.9	724	270	180
95	19	2.51	11.55	2	15.7	981	330	215
120	37	2.02	13	2.4	18	1245	380	240
150	37	2.24	14.41	2.4	19.4	1508	440	280
185	37	2.51	16.16	2.4	21.1	1866	520	320
240	37	2.87	18.51	2.4	23.5	2416	580	360

* NO MÁS DE 3 CONDUCTORES POR DUCTO TEMPERATURA AMBIENTE 30°C

MATRÍCULA	DESCRIPCIÓN
5021457	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 4v COLOR VERDE 450 / 750V
5021458	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 4 mm ² COLOR AMARILLO 450 / 750V
5021461	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 4 mm ² COLOR ROJO 450 / 750V
5021460	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 4 mm ² COLOR BLANCO 450 / 750V
5021462	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 4 mm ² COLOR AZUL 450 / 750V
5021464	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 6 mm ² COLOR AZUL 450 / 750V
5021465	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 6 mm ² COLOR NEGRO 450 / 750V
5021470	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 10 mm ² COLOR AMARILLO 450 / 750V
5021471	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 10 mm ² COLOR ROJO 450 / 750V
5021472	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 10 mm ² COLOR BLANCO 450 / 750V
5021473	CABLE THW 1x16 mm ² 750V NEGRO
5021475	CABLE THW 1x25 mm ² 750V NEGRO
5021477	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 35 mm ² COLOR NEGRO 450 / 750V
5021478	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 35 mm ² COLOR AMARILLO 450 / 750V
5021479	CABLE THW 1x50 mm ² 750V NEGRO
5021481	CABLE THW 1x70 mm ² 750V NEGRO
5021480	CONDUCTOR CABLEADO THW.600V. UNIPOLAR NEGRO 1x95 mm ²
5021483	CONDUCTOR CABLEADO THW.600V. UNIPOLAR 1x120 mm ²
5021485	CONDUCTOR CABLEADO THW.600V. UNIPOLAR 1x150 mm ²
5021487	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 185 mm ² COLOR NEGRO 450 / 750V
5021492	CONDUCTOR CABLEADO UNIPOLAR TIPO THW 240 mm ² C/AISLAMIENTO PVC 750V