

CONDUCTOR TIPO TW



TABLA DE DATOS TÉCNICOS TW (mm²)

CALIBRE CONDUCTOR mm ²	Nº HILOS	DIÁMETRO HILO mm	DIÁMETRO CONDUCTOR mm	ESPESOR AISLAMIENTO mm	DIÁMETRO EXTERIOR mm	PESO Kg/Km	AMPERAJE (*)	
							AIRE A	DUCTO A
ALAMBRES								
1.5	1	1.4	1.4	0.75	2.9	20	16	13
2.5	1	1.74	1.74	0.8	3.3	31	27	22
4	1	2.21	2.21	0.8	3.9	45	32	28
CABLES								
16	7	1.69	4.67	1.5	7.1	193	90	62
25	7	2.13	5.88	1.5	8.4	290	120	80
35	7	2.51	6.92	1.5	9.6	390	150	100
70	19	2.13	9.78	2	14.7	745	230	150
120	37	2.02	13	2.4	19	1280	320	210
* NO MÁS DE 3 CONDUCTORES POR DUCTO TEMPERATURA AMBIENTE 30°C								

MATRÍCULA	CONDUCTORES SÓLIDOS TIPO TW.
5021041	CONDUCTOR SÓLIDO TW 750V UNIP.AZUL 1 X 1.50MM2.
5021043	CONDUCTOR SÓLIDO TW 750V UNIP.AMARI. 1 X 1.50MM2.
5021045	CONDUCTOR SÓLIDO TW 750V UNIP.NEGRO 1 X 1.50MM2.
5021047	CONDUCTOR SÓLIDO TW 750V UNIP.ROJO 1 X 1,50MM2.
5021049	CONDUCTOR SÓLIDO TW 750V UNIP.VERDE 1 X 1.50MM2.
5021081	CONDUCTOR SÓLIDO TW 750V UNIP.AZUL 1 X 2.5MM2.
5021083	CONDUCTOR SÓLIDO TW 750V UNIP.AMARI. 1 X 2.5MM2.
5021085	CONDUCTOR SÓLIDO TW 750V UNIP.NEGRO 1 X 2,5MM2.
5021087	CONDUCTOR SÓLIDO TW 750V UNIP.ROJO 1 X 2.5MM2.
5021089	CONDUCTOR SÓLIDO TW 750V UNIP.VERDE 1 X 2.5MM2.
5021112	CONDUCTOR CABLEADO UNIPOLAR TIPO TW 4MM2 COLOR ROJO 450 / 750V
5021113	CONDUCTOR CABLEADO UNIPOLAR TIPO TW 4MM2 COLOR VERDE 450 / 750V
5021115	CONDUCTOR CABLEADO UNIPOLAR TIPO TW 4MM2 COLOR AZUL 450 / 750V
5021116	CONDUCTOR CABLEADO UNIPOLAR TIPO TW 4MM2 COLOR NEGRO 450 / 750V
MATRÍCULA	CONDUCTOR CABLEADO UNIPOLARES TIPO TW.
5021243	CONDUCTOR CABLEADO UNIPOLAR TIPO TW 16MM2 COLOR AMARILLO 450 / 750V
5021283	CONDUCTOR CABLEADO TW 750V UNIP. AMARI. 1X25MM2.
5021303	CONDUCTOR CABLEADO TW 750V UNIP. AMARI. 1X35MM2.
5021333	CONDUCTOR CABLEADO TW 750V UNIP. AMARI. 1X70MM2.
5021355	CONDUCTOR CABLEADO TW 750V UNIP. AMARI. 1X120MM2.